
Victoriana - 1 Drawer 2 Door Robe

Assembly Instructions - Please keep for future reference

230/2146

230/6142



Dimensions

Width - 72cm

Depth - 49cm

Height - 195cm



Important - Please read these instructions fully before starting assembly

If you need help or have damaged or missing parts, call the Customer Helpline: 08456 400800



!\ Safety and Care Advice

Important - Please read these instructions fully before starting assembly

- Warning: This unit weighs approximately 48kgs. Please lift with care.
- Check you have all the components and tools listed on pages 1, 2 and 3.
- Remove all fittings from the plastic bags and separate them into their groups.
- Keep children and animals away from the work area, small parts could choke if swallowed.
- Parts of the assembly will be easier with 2 people.

- Make sure you have enough space to layout the parts before starting.
- Do not stand or put weight on the product, this could cause damage.
- Assemble the item as close to its final position (in the same room) as possible.
- Assemble on a soft level surface to avoid damaging the unit or your floor (use opened out unit carton).



 We do not recommend the use of power drill/drivers for inserting screws,

as this could damage the unit. Only use hand screwdrivers.

- Safety note: It is recommended that this unit is secured to a wall using the bracket supplied.
- Dispose of all packaging carefully and responsibly.

Care and maintenance

• Only clean using a damp cloth and mild detergent, do no use bleach or abrasive cleaners.

Scissors

- From time to time check that there are no loose screws on this unit.
- This product should not be discarded with household waste. Take to your local authority waste disposal centre.

Tools required Eye protection Rule Spirit (when using a Cross-head level hammer or drill) screwdriver Electric drill (do not use

Bradawl

Hammer

Note: If required the next page can be cut out and used as reference throughout the assembly. Keep this page with these instructions for future reference.

Step ladder

for fitting


screws)

Square

Components - Panels

If you have damaged or missing components, call the **Customer Helpline: 08456 400800** *quoting the reference numbers below*

Please check you have all the panels listed below




(659 x 123mm)


Components - Fittings

If you have damaged or missing components, call the **Customer Helpline: 08456 400800** quoting the reference numbers below

Please check you have all the fittings listed below

Note: The quantities below are the correct amount to complete the assembly. In some cases more fittings may be supplied than are required.






If you have damaged or missing components, call the Assembly Instructions Customer Helpline: 08456 400800 quoting the reference numbers below

Step 1

Prepare the drawer front

Screw 2 metal dowels A into the drawer front 6.

Note: Tighten the metal dowels up fully against the panels.




Step 2

Prepare the drawer sides

Insert a small locking nut C into the hole shown on the left drawer side 8 and the right drawer side 9.

Note: The arrow on the locking nut **must** point towards the hole in the edge of the panel.




Step 3

Attach the drawer sides to the drawer front

Push the left drawer side 8 and right drawer side 9 onto the back of the drawer front 6.

Turn the small locking nuts **C** on the left drawer side 8 and right drawer side 9.

Note: Turn the locking nuts C clockwise to secure panels - more than 1/2 a turn.



Step 4

Fit the drawer base

Slide the drawer base 7 down the grooves in the large drawer sides 8 and 9 and down into the groove in the large drawer front 6.

Step 5

Fit the large drawer back

Fit the drawer back 10 between the drawer sides 8 and 9. Make sure that the drawer base 7 fits into the groove in the drawer back 10.

Hold the drawer back 10 in position and tap the knock-in pegs through the holes in the drawer sides 8 and 9.

8 6 F

9


7

8

Step 6

Attach the handles


Attach 2 handles **(R)** to the drawer front **(6)** using screws **(1)**.




Step 7

Fit the wedgefixes

Turn the large drawer assembly over and slide 4 wedgefixes **M** into the front and back grooves, as shown, and tighten up the screws.





Step 8

Prepare the left side


a: Fit 3 hinge plates P
to the left side 1
making sure that the slot
is facing towards the
finished front edge.


Push a rail holder N into the left side 1. Make sure that it is fitted straight, in line with the panel edges and then secure with screw 1.

Place a runner S onto the left side 1. Slide back the top of runner and use the 2nd hole from the front to fit the 1st screw 1.

Screw a metal dowel **A** into the left side **1**.

b: Slide the runner S back the other way and fit the 2nd screw into the corresponding hole in the left side 1.





Step 9

Prepare the right side


a: Fit 3 hinge plates P
to the right side 2
making sure that the slot
is facing towards the
finished front edge.

Push a rail holder N into the right side 2. Make sure that it is fitted straight, in line with the panel edges and then secure with screw 1.

Place a runner sonto the right side 2. Slide back the top of runner and use the 2nd hole from the front to fit the 1st screw 1.

Screw a metal dowel **A** into the right side **2**.


b: Slide the runner S back the other way and fit the 2nd screw into the corresponding hole in the right side 2.



Step 10

Fit the horizontal to the right side

Attach the horizontal 5 to the right side 2 using 2 screws **G**.



Step 11


Prepare the back rail

Insert 2 large locking nuts **3** into the back rail **12**.

Note: The arrow on the locking nut **must** point towards the hole in the edge of the panel.

Tap 2 wooden dowels **D** into the back rail **12**.

Note: Wooden dowels must not stick out from the edge by more than 10mm or they may damage other panels.




Step 12

Fit the back rail to the right side

Push the back rail 12 onto the right side 2.

Use a screwdriver to tighten the large locking nut **B** fitted to the back rail **12**.

Note: Turn the large locking nut 3 as far as it will go - more than 1/2 a turn.




Step 13

Fit the left side

Push the left side 1 onto the horozontal 5 and back rail 12.

Attach the left side 1 to the horizontal 5 using 2 screws **G**.

Use a screwdriver to tighten the large locking nut **B** fitted to the back rail **12**.




Step 14

Fit the top

Attach the top 3 to the left side 1 and right side 2 using 4 screws G.

Note: To make it easier to fit the top and base panels, place polystyrene blocks from the packaging underneath the side panels to raise the assembly.




Step **15**

Fit the base

Attach the base 4 to the left side 1 and right side 2 using 4 screws G.






Step 16

Fit the feet

Fit the 4 feet **1** to the base **4** using 4 screws **0** and tighten them using the allen key **0**.

Note: You may find it easier to turn the foot as the screw is held with the allen key.



Step 17

Fit the back

a: Square up the unit by making sure that measurement **x** to **x** equals **y** to **y**.

b: Place the back 14 onto the unit.

Nail **around the** outside edges of the back **14**.

Note: Nails should be spaced about 150mm apart.

Stand the unit up for the next step.



Warning: The unit is heavy. Lift with care.

Step 18


Fit the drawers


Slide both the runners of forward and locate the drawer sides and between them, lining up the holes in the drawer sides with the 2nd 'threaded' holes in the runners of.


Working from the inside of the drawer, insert 2 screws • through the drawer sides and out into the 2nd threaded hole in the runner.

Note: Do not overtighten the screws **①**. If they catch on the runner you may need to loosen them slightly.

The measurement from top corner X to bottom corner X must be equal to the measurement from top corner Y to bottom corner Y








Step 19

Fit the hanging rail

Push hanging rail 11 into the rail holders (1) fitted to the side panels.




Step 20

Prepare the 2 doors

Push fit 3 hinges **Q** into each of the 2 doors **13**.

Secure each hinge with 2 screws .

Note: Before securing with the screws, make sure that the hinges are positioned at 90 degrees with the edge of the door.



Step 21

Fit doors and handles

Note: The easiest way to attach each door 13 is to fit the top hinge first, then align and fit the other hinges.

a: Push the hinge Q onto the front part of the hinge plate P.


The recess at the bottom of screw B goes into the slot in the hinge plate.

b: Keep the hinge **Q** FLAT against the hinge plate **P** as you slide it across as far as it will go. Tighten screw A.

C: The hinge @ must be flat against the hinge plate P prior to any adjustment.

d: The hinge @ must NOT be AT AN ANGLE to the hinge plate P when assembled. This would indicate that the recess at the bottom of screw B had not located in the slot in the hinge plate and the hinge would not be secure. Remove the hinge from the hinge plate and then re-assemble being careful to follow instructions a-c.

e: Attach a handle **R** to each door **13** using screw **H**.



Step 22

Adjust the doors if needed

a: Before adjusting the doors, use a spirit level to check the base (or top) of the unit is level, front-to-back and side-to-side in the 3 positions shown.

Use suitable packing pieces (not supplied) to make the unit level BEFORE making any adjustment to the hinges, as shown.

b: Height adjustment.


Loosen screws A on hinge plates and move door up or down as required. Retighten screw A.

C: Forward and Back adjustment.

Loosen screw B on hinge plate and move door in or out as required. Retighten screw B.

d: Sideways adjustment.

To move door 'out' loosen screw C.
To move door 'in' tighten screw C.



Step 23

Attach bracket to top

To prevent possible overbalancing, we recommend that this unit is secured to a suitable wall by use of the bracket • fitted to the top of the unit.

Fixings are not supplied, as they will need to suit the wall type and the length of screw will depend on the distance from the back of the unit to the wall.

Fix the bracket older loosely onto the top of the unit using screw and mark the wall for the wall fixing.

Swivel the bracket **o** away from the wall and drill a hole in the wall using a suitable drill bit and fit your wall fixing.


Swivel the bracket oback and fix the bracket to the wall, then tighten screw **K**.

Note: Take care when drilling the wall that you do not drill into any pipes, wires etc. If in doubt, consult an expert.



Warning: The unit is heavy. Lift with care.

Assembly is complete



If you need help or have damaged or missing parts, call the **Customer Helpline: 08456 400800** and quote the reference numbers on the component pages.

Argos Ltd, 489-499 Avebury Boulevard, Central Milton Keynes, MK9 2NW

15 ALR3059