

life reimagined

USER'S OPERATION MANUAL

Before operating this unit, please read this manual thoroughly, and retain for future reference

RB403N4EB1 RB403N4EW1 RB403N4EY1 RB403N4EC1 RB403N4EC2

English

Contents

| Safety and warning information | 2 | |
|--------------------------------|----|--|
| Installing your new appliance | 9 | |
| Description of the appliance | 14 | |
| Display controls | 16 | |

| Using your appliance | 18 |
|---------------------------|----|
| Helpful hints and tips | 19 |
| Cleaning and care | 20 |
| Troubleshooting | 21 |
| Disposal of the appliance | 23 |



This appliance is in accordance with the following EU guidelines:2006/95/EC and 2004/108/EC and 2009/125/EC and EC.643/2009 and 2002/96/EC



Safety and warning information

For your safety and correct usage, before installing and first using the appliance, read this user manual carefully, including its hints and warnings. To avoid unnecessary mistakes and accidents, it is important to make sure that all people using the appliance are thoroughly familiar with its operation and safety features. Save these instructions and be sure that they remain with the appliance if it is moved or sold, so that anyone using it throughout its life, will be properly informed on its usage and safety notices.

For the safety of life and property, keep the precautions of these user's instructions as the manufacturer is not responsible for damages caused by omission.

Safety for children and others who are vulnerable people

This appliance can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved.

- Children shall not play with the appliance. Cleaning and user maintenance shall not be made by children without supervision.
- Keep all packaging away from children as there is risk of suffocation. If you are discarding the appliance, pull the plug out of the socket, cut the connection cable (as close to the appliance as you can) and remove the door to prevent children playing from suffering an electric shock or from closing themselves inside it.
- If this appliance, featuring a magnetic door seals, is to replace an older appliance having a spring lock (latch) on the door or lid, be sure to make the spring lock unusable before you discard the old appliance. This will prevent it from becoming a death trap for a child.

General safety

♠ • WARNING — This to be used in household and similar applications such as -staff kitchen areas in shops, offices and other working environments: -farm houses and by clients in hotels. motels and other residential type environments: -bed and breakfast type environments: -catering and similar non-retail applications

- WARNING Do not
- store explosive substances such as aerosol cans with a flammable propellant in this appliance.
- WARNING If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid a hazard.

- WARNING Keep ventilation openings, in the appliance enclosure or in the built-in structure, clear of obstruction.
- WARNING Do not use mechanical devices or other means to accelerate the defrosting process, other than those recommended by the manufacturer.
- WARNING Do not damage the refrigerant circuit.
- WARNING Do not use electrical appliances inside the food storage compartments of the appliance, unless they are of the type recommended by the manufacturer.
- WARNING The refrigerant and insulation blowing gas are flammable. When disposing of the appliance, do so only at an authorized waste disposal centre. Do not expose to flame.

Refrigerant

The refrigerant isobutene (R600a) is contained within the refrigerant circuit of the appliance, a natural gas with a high level of environmental compatibility, which is nevertheless flammable. During transportation and installation of the appliance, ensure that none of the components of the refrigerant circuit becomes damaged. The refrigerant (R600a) is flammable.



Caution:risk of fire

If the refrigerant circuit should be damaged:

- -Avoid opening flames and sources of ignition.
- -Thoroughly ventilate the room in which the appliance is situated.

It is dangerous to alter the specifications or modify this product in any way.

Any damage to the cord may cause a shortcircuit, fire, and/or electric shock.



Electrical safety

- 1.The power cord must not be lengthened.
- 2. Make sure that the power plug is not crushed or damaged. A crushed or damaged power plug may overheat and cause a fire.
- 3. Make sure that you can access the main plug of the appliance.
- 4. Do not pull the main cable.
- 5. If the power plug socket is loose, do not insert the power plug. There is a risk of electric shock or fire.
 6. You must not operate the
- appliance without the interior lighting lamp cover.
 7. The fridge is only applied with power supply of single phase alternating current of

220~240V/50Hz. If fluctuation of voltage in the district of user is so large that the voltage exceeds the above scope, for safety sake, be sure to apply A.C. Automatic voltage regulator of more than 350W to the fridge.

The fridge must employ a special power socket instead of common one with other electric appliances. Its plug must match the socket with ground wire.

Daily use

- Do not store flammable gass or liquids in the appliance, There is a risk of an explosion.
- Do not operate any electrical appliances in the appliance(e.g.electric ice cream makers, mixers etc.).
- When unplugging always pull the plug from the mains socket, do not pull on the cable.
- Do not place hot items near the plastic components of this appliance.

- Do not place food products directly against the air outlet on the rear wall. Store pre-packed frozen food in accordance with the frozen food manufacture's instructions. The appliances manufactures storage recommendations should be strictly adhered to Refer to refrelevant instructions for storage.
- Do not place
 carbonated or fizzy
 drinks in the freeze
 compartment as it
 creates pressure on
 the container, which
 may cause it to
 explode, resulting in
 damage to the
 appliance.
 Frozen food can cause
 frost burns if
 consumed straight
 from the freezer
 compartment.

- Do not place the appliance in direct sunlight.
 Keep buring candles, lamps and other items with naked flames away from the appliance so that do not set the appliance on fire.
- The appliance is intended for keeping food stuff and/or beverages in normal household as explained in this instruction booklet The appliance is heavy. Care should be taken when moving it.
- Do not remove nor touch items from the freezer compartment if your hands are damp/wet,as this could cause skin abrasions or frost/freezer burns.
- Never use the base, drawers, doors etc. to stand on or as supports.
- Frozen food must not be refrozen once it has been thawed out.

- Do not consume ice popsicles or ice cubes straight from the freezer as this can cause freezer burn to the mouth and lips.
- To avoid items falling and causing injury or damage to the appliance, do not overload the door racks or put too much food in the crisper drawers.

caution! Care and cleaning

Before maintenance, switch off the appliance and disconnect the mains plug from the mains socket.

- Do not clean the appliance with metal objects, steam cleaner, ethereal oils, organic solvents or abrasive cleansers.
- Do not use sharp objects to remove frost from the appliance. Use a plastic scraper.

Installation Important!

- For electrical connection carefully, follow the instructions given in this manual.
- Unpack the appliance and check if there are damages on it. Do not connect the appliance if it is damaged. Report possible damages immediately to the place you bought it. In this case retain packing.
- It is advisable to wait at least four hours before connecting the appliance to allow the oil to flow back in the compressor.
- Adequate air circulation should be around the appliance, lacking this leads to overheating. To achieve sufficient ventilation, follow the instructions relevant to installation.
- Wherever possible the back of the product should not be too close to a wall to avoid touching or catching warm parts (compressor,

- condenser) to prevent the risk of a fire, follow the instructions relevant to installation.
- The appliance must not be locate close to radiators or cookers.
- Make sure that the mains plug is accessible after the installation of the appliance.

Service

- Any electrical work required to do the servicing of the appliance should be carried out by qualified electrician or competent person.
- This product must be serviced by an authorized Service Center, and only genuine spare parts must be used.
 1)If the appliance is Frost Free.
 - 2)If the appliance contains freezer compartment.

Installing your new appliance

Before using the appliance for the first time, you should be informed of the following tips.


Ventilation of appliance

In order to improve efficiency of the cooling system and save energy, it is necessary to maintain good ventilation around the appliance for the dissipation of heat. For this reason, sufficient clear space should be available around the refrigerator.

Suggest :It is advisable for there to be at least 75mm of space from the back to the wall, at least 100mm from its

top,at last 100mm from its side to the wall and a clear space in front to allow the doors to open 135°. As shown in following diagrams.





Note:


• This appliance performs well within the climate class showed in the table below. It may not work properly if being left at a temperature above or below the indicated range for a long period.

| Climate class | Ambient temperature |
|---------------|---------------------|
| SN | +10°C to +32°C |
| N | +16°C to +32°C |
| ST | +16°C to +38°C |
| Т | +16°C to +43°C |

- •Stand your appliance in a dry place to avoid high moisture.
- Keep the appliance out of direct sunlight, rain or frost. Stand the appliance away from heat sources such as stoves, fires or heaters.

Leveling of appliance

- For sufficient leveling and air circulating in the lower rear section of the appliance, the bottom feet may need to be adjusted. You can adjust them manually by hand or by using a suitable spanner.
- To allow the doors to self-close, tilt the top backwards by about 10mm.




Reversing the door

The side at which the door opens can be changed, from the right side (as supplied) to the left side, if the installation site requires.


Warning! When reversing the door, the appliance must not be connected to the mains. Ensure that the plug is removed from the mains socket..

Tools you will need




Note: Before you start lay the refrigerator on its back in order to gain access to the base, you should rest it on soft foam packaging or similar material to avoid damaging the backboard of the refrigerator. To reverse the door, the following steps are generally recommended.

1. Stand the refrigerator upright. Open the upper door to take out all door racks (to avoid racks damaged) and then close the door.



2. Open part ① on top of the refrigerator body from right side and then take down part ③ and part ④ on the upper door in the same way. Take down part ② and put it back to the plastic bag.



3. Take down the corner cover.




4. Remove the screws ① , and remove part②.



Note: Please hold the upper door by hand during step 4 to prevent door dropping.

5. Remove the upper door and place it on a smooth surface with its panel upwards. Loose screws³, detach part ² and part ¹ then install part ¹ and

another part②(in the plastic bag)to the left side with screws③. Put part②just detached back to plastic bag.



6. Loose screws used to fix the middle hinge and remove middle hinge. Then remove the lower door.




7. Place the lower door on a smooth surface with its panel upwards. Loose screws③, detach part② and part①. Turn part① by 180°and then install① and part② to corresponding position on left side together with screws③.







8. Change screw hole covers on middle cover plate from left to right (as shown in figure below).




9. Place refrigerator flatwise, remove part③ and then loose screws④. Remove part ② and part①.



- 10. Screw out lower hinge, change it to the near hole site, and then screw up and mount washer
- 11.Just remount to the step 9,change part①to left and part②to right and then fix them with screws④. Finally install part③.




12. Move the lower door and adjust its position to align lower hole site and upper hinge axis. Turn the middle hinge by 180, change the washer on the axis to the upper side, adjust the middle hinge to the appropriate position and then install it.



13. Screw out The upper hinge axis, turn the upper hinge over and fix axis on it. Then place it at side for use.



14. Move the upper door to appropriate position, adjust part① and upper door, then fix part① by screws②. (Please hold upper door by hand when installing)



15. Install part the upper hinge cover (which is in the plastic bag).



16.Reverse part① by 180° and install it onto the right corner of upper door, then mount part②. (both of which are taken down in step 2)





17. install part① , and then install part②





18. Open the upper door, mount door racks and then close it.

Description of the appliance

1.Cabinet

2.Display board part

3.KED light

4 Glass shelf

5.Crisper cover

6. Fruit and vegetables crisper

7.Upper freezer drawer

8.Upper freezer glass shelf

9.Middle freezer drawer(huge box)

10.Middle freezer glass shelf

11.Lower freezer drawer

12.Adjustable bottom feet

13.Fridge door

14.Egg tray(in the shelf)

15.Middle fridge door shelf


16.Lower fridge door shelf

17.Fridge door seal

18.Freezer door seal

19.Freezer door

View of the appliance RB403N4EW1 RB403N4EY1 RB403N4EC1 RB403N4EB1




Note: Due to unceasing modification of our products, your refrigerator may be slightly different from this instruction manual, but its functions and using methods remain the same. To get more space in the freezer, you can remove drawers (except lower freezer drawer),installtion bracket and integrative ice maker/twistable ice tray.

Description of the appliance

- 1.Cabinet
- 2.Display board part
- 3.KED light
- 4.Glass shelf
- 5.Crisper cover
- 6. Fruit and vegetables crisper
- 7.Crisper cover of Moisture 0 Cool
- 8.Moisture 0 Cool
- 9.Upper freezer drawer
- 10.Upper freezer glass shelf
- 11.Middle freezer drawer(huge box)
- 12 Middle freezer glass shelf
- 13.Lower freezer drawer
- 14 Adjustable bottom feet
- 15.Fridge door
- 16.Egg tray(in the shelf)
- 17.Middle fridge door shelf
- 18.Lower fridge door shelf
- 19.Fridge door seal
- 20.Freezer door seal
- 21.Freezer door

View of the appliance


RB403N4EC2



Note: Due to unceasing modification of our products, your refrigerator may be slightly different from this instruction manual, but its functions and using methods remain the same. To get more space in the freezer, you can remove drawers (except lower freezer drawer),installtion bracket and integrative ice maker/twistable ice trav.

Display controls

Use your appliance according to the following control regulations, your appliance has the corresponding functions and modes as the control panels showed in the pictures below. When the appliance is powered on for the first time, the backlighting of the icons on display panel starts working. If no buttons have been pressed and the doors are closed, the backlighting will turn off.



Controlling the temperature

We recommend that when you start your refrigerator for the first time, the temperature for the refrigerator is set to 4°C and the freezer to -18°C. If you want to change the temperature, follow the instructions below.

Caution! When you set a temperature, you set an average temperature for the whole refrigerator cabinet. Temperatures inside each compartment may vary from the temperature values displayed on the panel, depending on how much food you store and where you place them. Ambient temperature may also affect the actual temperature inside the appliance.

1. Fridge

Press the middle part of button to set fridge temperature between 2°C and 8°C as needed, and control panel will display corresponding figures according to the following sequence.

2. Freezer

Press the middle part of button to set fridge temperature between -16°C and -24°C as needed, and control panel will display corresponding figures according to the following sequence.

3. Super Freeze

Freezer Hold 3 sec for

Super Freeze will quickly lower the temperature Super Freeze within the freezer so food will freeze vitamins and

nutrients of fresh food and keep food fresh longer.

- Press the middle part of Freeze button for 3 seconds to activate the super freeze function. The light swill come on.
- In case of the maximum amount of food to be frozen, please wait about 24
- Super freeze automatically switches off after 26 hours
- •When super freeze function is on you can switch off super freeze function by pressing the middle part of FORCET button and the freezer temperature setting will revert back to the previous setting.

4. Holiday

Fridae Hold 3 sec for Holiday

If you are going to be away for a long period of time, you can activate this function by pressing the

middle part of button for 3 seconds


- When the holiday function is activated, the temperature of the refrigerator is automatically switched to to minimize the energy consumption.Important! Do not store any food in the fridge during this time.
- When the holiday function is on, you can switch it off by pressing the middle part of Fridge button. The fridge temperature setting will revert back to the previous setting.

Using your appliance

You appliance has the accessories as the "Description of the appliance" showed in general, with this part instruction you can have the right way to use them.

Door rack

- It is suitable for the storage of eggs, canned liquid, bottled drinks and packed food, etc. Do not place too many heavy things in the racks
- The middle door shelf can be placed at different heights according to your requirements. Please take food out of the shelf before lifting vertically to reposition.



Note: There are egg trays in the upper shelf and bottle holder in the lower shelf.


Shelf in Refrigerator chamber

• There are shelves in refrigerator chamber, and they can be taken out to be cleaned



Folded shelf

- It is made up of fixed part and flexible part.
- It can be adjusted and folded to achieve different storage volume as you need. See the picture below:



Crisper cover

It is for controlling the temperature of the crisper and avoiding the vegetable losing moisture.

Crisper of refrigerator chamber

It is suitable for the storage of fruits and vegetable.

Moisture 0 Cool (only applicable to RB403N4EC2)

The temperature there is about 2-3°C lower than that in the refrigerator chamber.

It is used to store fish, meat and other erodible food.

Note: When selecting the Super Freeze function, ensure there is no bottled or canned liquid which could explode caused by volume expanding.

Freezer Drawer

It is used to store food which needs to be frozen, including meat, fish, ice cream, etc.

Helpful hints and tips

Energy saving tips

We recommend that you follow the tips below to save energy.

- Try to avoid keeping the door open for long periods in order to conserve energy.
- Ensure the appliance is away from any sources of heat (Direct sunlight, electric oven or cooker etc)
- Don't set the temperature colder than necessary.
- Don't store warm food or evaporating liquid in the appliance.
- Place the appliance in a well ventilated, humidity free, room. Please refer to Installing your new appliance chapter.
- If the diagram shows the correct combination for the drawers, crisper and shelves, do not adjust the combination as this is designed to be the most energy efficient configuration.

Hints for fresh food refrigeration

- •Do not place hot food directly into the refrigerator or freezer, the internal temperature will increase resulting in the compressor having to work harder and will consume more energy.
- Do cover or wrap the food, particularly if it has a strong flavor.
- •Place food properly so that air can circulate freely around it.

Hints for refrigeration

- Meat (All Types) Wrap in polythene food: wrap and place on the glass shelf above the vegetable drawer. Always follow food storage times and use by dates suggested by manufacturers.
- Cooked food, cold dishes, etc.:
 They should be covered and may be placed on any shelf.

Fruit and vegetables:

They should be stored in the special drawer provided.

Butter and cheese:

Should be wrapped in airtight foil or plastic film wrap.

film wrap.

• Milk bottles:

Should have a lid and be stored in the door racks.

Hints for freezing

- •When first starting-up or after a period out of use, let the appliance run at least 2 hours on the higher settings before putting food in the compartment.
- Prepare food in small portions to enable it to be rapidly and completely frozen and to make it possible to subsequently thaw only the quantity required.
- Wrap up the food in aluminum foil or polyethylene food wraps which are airtight,
- •Do not allow fresh, unfrozen food to touch the food which is already frozen to avoid temperature rise of the latter.
- Iced products, if consumed immediately after removal from the freezer compartment, will probably cause frost burns to the skin.

It is recommended to label and date each frozen package in order to keep track of the storage time.

Hints for the storage of frozen food

- Ensure that frozen food has been stored correctly by the food retailer
- Once defrosted, food will deteriorate rapidly and should not be re-frozen. Do not exceed the storage period indicated by the food manufacturer.

Switching off your appliance

If the appliance needs to be switched off for an extended period, the following steps should be taken prevent mould on the appliance.

1. Remove all food.

- 2. Remove the power plug from the mains socket.
- 3. Clean and dry the interior thoroughly.
- 4. Ensure that all the doors are wedged open slightly to allow air to circulate.

Cleaning and care

For hygienic reasons the appliance (including exterior and interior accessories) should be cleaned regularly at least every two months.

Caution! The appliance must not be connected to the mains during cleaning. Danger of electrical shock! Before cleaning switch the appliance off and remove the plug from the mains socket.

Exterior cleaning

To maintain good appearance of your appliance, you should clean it regularly.

- -Wipe the digital panel and display panel with a clean, soft cloth.
- -Spray water onto the cleaning cloth instead of spraying directly on the surface of the appliance. This helps ensure an even distribution of moisture to the surface.
- -Clean the doors, handles and cabinet surfaces with a mild detergent and then wiped dry with a soft cloth.

Caution!

- -Don't use sharp objects as they are likely to scratch the surface.
- -Don't use Thinner, Car detergent, Clorox, ethereal oil, abrasive cleansers or organic solvent such as Benzene for cleaning. They may damage the surface of the appliance and may cause fire.

Interior cleaning

You should clean the appliance interior regularly. It will be easier to clean when food stocks are low. Wipe the inside of the fridge freezer with a weak solution of bicarbonate of soda, and then rinse with warm water using a wrung-out sponge or cloth. Wipe completely dry before replacing the shelves and baskets.

Thoroughly dry all surfaces and removable parts.

Although this appliance automatically defrosts, a layer of frost may occur on the freezer compartment's interior walls if the freezer door is opened frequently or kept open too long. If the frost is too thick, choose a time when the supply of food stocks are low and proceed as follows:

- 1.Remove existing food and accessories baskets, unplug the appliance from the mains power and leave the doors open. Ventilate the room thoroughly to accelerate the thawing process.
- 2. When defrosting is completed, clean your freezer as described above.

Caution! Don't use sharp objects to remove frost from the freezer compartment. Only after the interior is completely dry should the appliance be switched back on and plugged back into the mains socket.

Door seals cleaning

Take care to keep door seals clean. Sticky food and drinks can cause seals to stick to the cabinet and tear when you open the door. Wash seal with a mild detergent and warm water. Rinse and dry it thoroughly after cleaning.

Caution! Only after the door seals are completely dry should the appliance be powered on.

Replacing the LED light:

Warning: The LED light must not be

replaced by the user! If the LED light is damaged, contact the customer helpline for assistance. To replace the LED light, the below steps can be followed:

- 1. Unplug your appliance.
- 2. Remove light cover by pushing up and out.
- 3. Hold the LED cover with one hand and pull it with the other hand while pressing the connector latch.
- 4. Replace LED light and snap it correctly in place.

Troubleshooting

If you experience a problem with your appliance or are concerned that the appliance is not functioning correctly, you can carry out some easy checks before calling for service, please see below. You can carry out some easy checks according to this section before calling for service.

Warning! Don't try to repair the appliance yourself. If the problem persists after you have made the checks mentioned below, contact a qualified electrician, authorized service engineer or the shop where you purchased the product.

| Drahlam | Descible serves 9 Calvition |
|----------------------------|--|
| Problem | Possible cause & Solution |
| | Check whether the power cord is plugged into the power outlet |
| | properly. |
| | Check the fuse or circuit of your power supply, replace if |
| Appliance is not working | necessary. |
| correctly | The ambient temperature is too low. Try setting the chamber |
| | temperature to a colder level to solve this problem. |
| | It is normal that the freezer is not operating during the |
| | automatic defrost cycle, or for a short time after the appliance |
| | is switched on to protect the compressor. |
| Odours from the | The interior may need to be cleaned |
| compartments | Some food, containers or wrapping cause odours. |
| | The sounds below are quite normal: |
| | Compressor running noises. |
| | •Air movement noise from the small fan motor in the freezer |
| | compartment or other compartments. |
| | Gurgling sound similar to water boiling. |
| Noise from the | Popping noise during automatic defrosting. |
| appliance | Clicking noise before the compressor starts. |
| | Other unusual noises are due to the reasons below and may |
| | need you to check and take action: |
| | The cabinet is not level. |
| | The back of appliance touches the wall. |
| | Bottles or containers fallen or rolling. |
| | It is normal to frequently hear the sound of the motor, it will |
| | need to run more when in following circumstances: |
| | Temperature setting is set colder than necessary |
| The motor runs | Large quantity of warm food has recently been stored within |
| continuously | the appliance. |
| Continuously | •The temperature outside the appliance is too high. |
| | Doors are kept open too long or too often. |
| | •After your installing the appliance or it has been switched off |
| | for a long time. |
| | Check that the air outlets are not blocked by food and ensure |
| A layer of frost occurs in | food is placed within the appliance to allow sufficient |
| the compartment | ventilation. Ensure that door is fully closed. To remove the |
| | frost, please refer to cleaning and care chapter. |
| | You may have left the doors open too long or too frequently; or |
| Temperature inside is | the doors are kept open by some obstacle; or the appliance is |
| too warm | located with insufficient clearance at the sides, back and top |
| Temperature inside is | Increase the temperature by following the "Display controls" |
| too cold | chapter. |
| Doors cant be closed | Check whether the top of the refrigerator is tilted back by |
| easily | 10-15mm to allow the doors to self close, or if something inside |
| | |

| | is preventing the doors from closing. |
|--------------------------|---|
| Water drips on the floor | The water pan (located at the rear bottom of the cabinet) may not be properly leveled, or the draining spout (located underneath the top of the compressor depot) may not be properly positioned to direct water into this pan, or the water spout is blocked. You may need to pull the refrigerator away from the wall to check the pan and spout. |
| The light is not working | ●The LED light may be damaged. Refer to replace LED lights in cleaning and care chapter. ●The control system has disabled the lights due to the door being kept open too long, close and reopens the door to reactivate the lights. |

Disposal of the appliance

It is prohibited to dispose of this appliance as household waste.

Packaging materials

Packaging materials with the recycle symbol are recyclable. Dispose of the packaging into a suitable waste collection container to recycle it.

Before disposal of the appliance

- 1. Pull out the mains plug from the mains socket.
- 2. Cut off the power cord and discard with the mains plug

Warning! Refrigerators contain refrigerant and gases in the insulation. Refrigerant and gases must be disposed of professionally as they may cause eye injuries or ignition. Ensure that tubing of the refrigerant circuit is not damage prior to proper disposal.

Correct Disposal of this product



This marking indicates that this product should not be disposed with other household wastes throughout the EU. To prevent possible harm to the environment or human health from uncontrolled waste disposal, recycle it responsibly to promote the sustainable reuse of material resources. To return your used device, please use the return and collection systems or contact the retailer where the product was purchased. They can take this product for environmental safe recycling.

Hisense Service Help Line: 0844 3460087



Hisense UK Ltd Unit D, Global Avenue Millshaw Leeds LS11 8PR

Tel: +44 (0) 113 395 6930 Fax: +44 (0) 113 270 8599