

FUJIFILM X-A10 Specifications

Model Name		FUJIFILM X-A10
Number of effective pixels		16.3 million pixels
Image sensor		23.6mm×15.6mm (APS-C) CMOS with primary color filter
Sensor Cleaning system		Ultra Sonic Vibration
Storage media		SD Card (-2G) / SDHC Card (-32G) / SDXC Card (-256G) UHS-I *1
File format	still image	JPEG (Exif Ver 2.3 *2) RAW (RAF format)/RAW+JPEG (Design rule for Camera File system compliant, DPOF-compatible)
	movie	Movie File Format : MOV Movie Video Compression : H.264 Audio : Linear PCM Stereo
Number of recorded pixels		L: (3:2) 4896 x 3264 / (16:9) 4896 x 2760 / (1:1) 3264×3264
		M: (3:2) 3456 x 2304 / (16:9) 3456 x 1944 / (1:1) 2304×2304
		S: (3:2) 2496 x 1664 / (16:9) 2496 x 1408 / (1:1) 1664×1664
		<Motion Panorama> 180°: Vertical: 2160 x 9600 / Horizontal: 9600 x 1440 120°: Vertical: 2160 x 6400 / Horizontal: 6400 x 1440
Lens mount		FUJIFILM X mount
Sensitivity		Standard Output Sensitivity : AUTO1 / AUTO2 / AUTO3(up to ISO6400) / ISO200 to 6400(1/3 step) Extended output sensitivity : ISO100 / 12800 / 25600
Exposure control		TTL 256-zones metering, Multi / Spot / Average
Exposure mode		P(Program AE) / S(Shutter Speed Priority AE) / A(Aperture Priority AE) / M(Manual Exposure)
Exposure compensation		-3.0EV - +3.0EV, 1/3EV step (movie recording : -2.0EV - +2.0EV)
Image Stabilizer		Supported with OIS type lens
Face Detection		Yes
Eye Detection		Yes
Shutter type		Focal Plane Shutter
Shutter speed	Mechanical Shutter	4 sec. to 1/4000 sec.(P mode), 30 sec. to 1/4000 sec.(All modes) Bulb mode(up to 60 min), TIME : 30 sec. to 1/4000 sec.
	Electronic Shutter *3	1 sec. to 1/32000 sec.(P / S / A / M modes) Bulb mode : 1 sec. fixed, TIME : 1 sec to 1/32000sec.
	Mechanical + Electronic Shutter	4 sec. to 1/32000 sec.(P mode), 30 sec. to 1/32000 sec.(All modes) Bulb mode(up to 60 min), TIME : 30 sec. to 1/32000 sec.
	Synchronized shutter speed for flash	1/180 sec. or slower
Continuous shooting		Approx. 6.0 fps (JPEG : max. approx. 20 frames) Approx. 3.0 fps (JPEG : up to the capacity of the card) *Recordable frame number may vary depending on the type of memory card used. *The frame rate varies with shooting condition and the number of images recorded.
Auto bracketing		AE Bracketing (±1/3EV, ±2/3EV, ±1EV) Film Simulation Bracketing (Any 3 types of film simulation selectable) Dynamic Range Bracketing (100%・200%・400%) ISO sensitivity Bracketing (±1/3EV, ±2/3EV, ±1EV) White Balance Bracketing (±1, ±2, ±3)
Focus	mode	Manual Focus / Multi AF / Area AF / Continuous AF / Tracking AF
	type	TTL contrast AF, AF assist illuminator available
	AF frame selection	Area AF (49 areas with 7 x 7), Changeable AF frame size
White balance		Automatic Scene recognition / Custom / Color temperature selection (2500K-10000K) / Preset: Fine,Shade, Fluorescent light (Daylight), Fluorescent light (Warm White), Fluorescent light (Cool White),Incandescent light, Underwater
Self-timer		2sec. / 10sec. / Smile / Buddy (LV.1 - LV.3) / Group (1-4 subjects)
Flash		Manual pop-up flash (Super Intelligent Flash) Guide number : Approx 5 (ISO100-m) / Approx 7 (ISO200-m)
Flash modes		Red-eye removal OFF: Auto/Forced Flash/Suppressed Flash/Slow Synchro/Rear-curtain Synchro/Commander Red-eye removal ON: Red-eye Reduction Auto/Red-eye Reduction & Forced Flash/Suppressed Flash/ Red-eye Reduction & Slow Synchro/Red-eye Reduction & Rear-curtain Synchro/Commander *Red-eye removal is active when Face Detection is set to ON.

For more information, please visit our website:

<http://fujifilm-x.com/x-a10/>

To ensure correct usage, read owner's manual carefully before using your equipment.

All photos, illustrations, drawings and other images in this brochure are intended for illustrative purposes only.

DXC logo is a trademark. All other trademarks are the property of their respective holders.

SILKYPiX® is a registered trademark of Ichikawa Soft Laboratory Co., Ltd. in Japan.

Hot shoe		No
LCD monitor		3.0-inch, aspect ratio 3:2, approx. 1,040K-dot Tilt-type, TFT color LCD monitor (approx. 100% coverage)
Movie recording		Full HD 1920 x 1080 30p / 25p / 24p, Continuous recording : up to approx. 14 min. HD 1280 x 720 60p / 50p / 24p, Continuous recording : up to approx. 27 min. *Use a card with SD Speed Class with CLASS10 or higher
Mode dial		Advanced SR AUTO / P / S / A / M / C(Custom) / Night / Sports / Landscape / Portrait Enhancer / SP(Scene Position) / Adv.
Film Simulation mode		6 type (PROVIA/STANDARD, Velvia/VIVID, ASTIA/SOFT, CLASSIC CHROME, MONOCHROME, SEPIA)
Dynamic range setting		AUTO, 100%, 200%, 400% ISO restriction (DR100%: No limit, DR200%: ISO400 or more, DR400%: ISO800 or more)
Advanced filter		Toy camera, Miniature, Pop color, High-key, Low-key, Dynamic tone, Fish-eye, Soft focus, Cross screen, Partial color (Red / Orange / Yellow / Green / Blue / Purple)
Touch screen		No
Other photography functions		Advanced SR AUTO, Eye detection AF, Face Detection, Interval timer shooting, Auto Red-eye Removal, Select custom setting, Motion panorama, Color space, Setting (Color, Sharpness, D-range, Gradation), Film Simulation, Advanced Filter, Framing guideline, Frame No. memory, Histogram display, Preview depth of focus, Focus check, Focus Peak Highlight, Multiple exposure, Fn button setting, ISO AUTO control, Interlock spot AE & Focus area, Edit/Save quick menu, Preview exp./ WB in manual mode, Shutter Type
Playback functions		RAW conversion, Image rotate, Auto image rotate, Face Detection, Red-eye reduction, Photobook assist, Erase selected frames, Multi-frame playback (with micro thumbnail), Slide show, Protect, Crop, Resize, Panorama, Favorites
Wireless transmitter	standard	IEEE 802.11b/g/n (standard wireless protocol)
	access mode	Infrastructure
Wireless function		Geotagging setup, Image transfer (Individual image/Selected multiple images), View & Obtain Images, PC Autosave, instax Printer Print
Other functions		35 Languages, Date/Time, Time difference, Sound & Flash OFF, Quick start Mode, High Performance, Preview exp. in Manual mode, LCD Brightness, LCD Color, Preview Pic. Effect, DISP. Custom Setting
Terminal	Video output	—
	Digital interface	USB 2.0 High-Speed / micro USB terminal *connectable with Remote Release RR-90 (sold separately)
	HD output	HDMI Micro connector (Type D)
Power supply		NP-W126S Li-ion battery (included)
Dimensions		116.9(W) mm x 67.4 (H) mm x 40.4(D) mm / 4.6 in.(W) x 2.7 in. (H) x 1.6 in. (D) (Minimum depth: 32.1 mm/ 1.3 in.)
Weight		Approx. 331g / 11.7 oz. (including battery and memory card) Approx. 282g / 9.9 oz. (excluding accessories, battery and memory card)
Operating	Temperature	0 - 40°C / 32-104°F
	Humidity	10 - 80% (no condensation)
Battery life for still images *4		approx 410 frames (with XF35mmF1.4 R lens)
Starting up period		Approx. 0.7 sec., when High Performance mode set to ON Approx. 1.3 sec., when High Performance mode set to OFF *Fujifilm research
Accessories included		Li-ion battery NP-W126S, AC power adapter AC-5VF, Plug Adapter, USB cable, Shoulder strap, Body cap, Owner's manual

*1 Please see the Fujifilm website (http://www.fujifilm.com/support/digital_cameras/compatibility/card/x/) to check memory card compatibility.

*2 Exif 2.3 is a digital camera file format that contains a variety of shooting information for optimal printing.

*3 The Electronic Shutter may not be suitable for fast-moving objects. Flash can not be used.

*4 Approximate number of frames that can be taken with a fully-charged battery based on CIPA standard.



Specifications are subject to change without notice

For more information, please visit our website

http://www.fujifilm.com/products/digital_cameras/index.html

FUJIFILM
Value from Innovation



X-A10

X-A10

The X-A10 - a compact and stylish camera packed with features perfect for everyday use

Featuring the beautiful color reproduction and advanced shooting performance found in all X Series cameras, the X-A10 also helps you capture everyday life perfectly thanks to its 180° tilting LCD screen, macro shooting from as close as 7cm, and Super Intelligent Flash that naturally captures backgrounds.



- * Capture your life in style with Selfie mode
- * In-built Portrait Enhancer helps you capture beautiful images of you and your friends
- * Three types of Self Timer mean you'll never miss a smile
- * Macro mode lets you get up close and personal with your favourite things
- * Get creative with different "Film Simulation" modes

