
Babystart 3 wheeler

User Guide



Cat No.:910/4323(D)

Helpline:03456 400 800

up to 33lbs 15kg

IMPORTANT: KEEP FOR FUTURE REFERENCE


Thank you for choosing our product. Please always read all the instructions povided carefully before use and remember, Your child's safety may be affected if you don't follow these instructions.

The stroller is suitable for children under 36 months. The max load of the stroller is 15kg. Never overload.


- **WARNING:** Do not use if any part is broken,torn or missing .
- **WARNING: Never leave your child unattended.**
- **WARNING:** This seat unit is not suitable for children over 36 months.
- **WARNING:** Accessories which are not approved by the manufacturer shall not be used.
- **WARNING:** Avoid placing the stroller near naked heat sources such as electric bar fires, gas fires, etc. or where a child could gain access to any other kinds of hazards.
- **WARNING: Always use the crotch strap in combination with the waist belt.**
- **WARNING:** Always use the harness provided and make sure the harness is correctly fitted.
- **WARNING: Any load attached to the handle affects the stability of the stroller.**
- **WARNING: Ensure that all the locking devices are engaged before use.**
- **WARNING: This product is not suitable for running or skating .**
- **WARNING:** To avoid injury ensure that your child is kept away when unfolding and folding this product.
- **WARNING:** Do not let your child play with this product.
- **WARNING:** Use the stroller for only one child at a time.
- **WARNING:** The maximum permissible loading for shopping basket is 5 kg.
- **WARNING: Please use the most reclined position for new born babies.**
- **WARNING: Ensure that the parking device shall be engaged when placing and removing the children.**

Part list


Front wheel



Rear wheel




bumper bar




Part list

Frame with fabric cover



Raincover




Footmuff



Assembly

Step 1


Unfold frame:(pic.1)
Release folding hook first as picture, take hold of handle and lift up by two hands,until hear a "click", then press down the handle support lock to lock the system.



1

Step 2

Front wheel installation: (Pic.2)Insert front wheel axle into the front frame until you hear a"click", that indicates install correct.
Remove front wheel: press the button and pull out the wheel.




2

Step 3

Rear wheel installation: (Pic.3) Insert rear wheel pin into the rear wheel house, until hear a "click".
Remove rear wheel: Press the lock plate button as picture and pull the rear wheels out.

WARNING: Please ensure the lock pin has been fully locked in the plastic house.




3

Use

Step 4


Install bumper bar:(Pic.4) Insert the end of bumper bar into each adaptor, until hear a "click".
Disassemble:
Press down the release button one each side, then pull the bumper bar out.



4

Step 5


Adjust backrest: (pic. 5)Press the button of adjustable buckle and Pull or push the webbing to your wanted position.



5

Step 6


Use the front swivel lock: (pic. 6)Press on the swivel lock to fix the direction of front wheels, and uplift it to turn its free direction.



6

Step 7

Safety belt adjustment: (pic. 7) Plug : Bring two clips together and plug them into the socket until you hear a click, that indicates locked.
Release:Press the button at both sides, and pull out the two clips, then the safety belt will be released.
Shorten:draw out the top tach belt, then draw out the end belt, locking.
Elongate:draw out the top tach belt, then draw back the end belt , locking.




Please ensure the pushchair as locking state before you prepare to put your baby in it.

7

Step 8

Link brake bar operation: (pic. 8) Press the red brake pedal on right side of rear wheels to set the brake, until hear a "click", indicates the pushchair locked.
Lift the blue brake pedal to unbrake the pushchair.


WARNING: Please always apply parking brake when you stop moving.



8

Step 9


Adjust canopy : (pic.9) Pull or push the canopy strip front per picture,the canopy can be adjusted.




9

Step 10

Install footmuff (Pic.10)
1、Insert footmuff from footrest and fit the buckle on both sides of footmuff and canopy.
2、Let the velcro on both sides pass round rear wheels frame and fixed.
3、Fit the velcro on front of footmuff around front wheels frame. The completely installation as Pic.10c.



10a




10b




10c

Step 11

Insert raincover: (pic. 11)Insert raincover from canopy and handle bar, fix the hook and lop of handle position, let the hook and lop of front go through front wheel frame and fixed.
The completely installation as Pic.11b.




11a



11b

Step 12


Folding operation: (Pic.12)
Press the folding button of Pic.1 and lift it, then press down the button of number 2 and number 3 at the same time, the pushchair can be folded. The folding direction per Pic.12b. Last locking the folding hook as Pic.12c.



12a



12b



12c

Care and Maintenance

General:

This pushchair was designed and manufactured with quality materials and craftsmanship. Always use the safety harness.

Lubricate moving parts regularly, especially the wheels, and lower parts of the chassis that tend to collect dirt.

Inspect regularly for:

- Worn parts, torn materials or stitching.
- Loose screws ,bent or broken frame parts .
- Broken, damaged or missing parts.

Should any of the above be evident do not use and contact the Helpline:03456 400 800 for advice.

Care and Maintenance:

Fabric parts may be cleaned in accordance with the fabric care labels. Do not machine wash.
Seat: Sponge clean only.
Canopy/Basket:Hand wash only.
Do not leave the stroller exposed to heat i.e. by a radiator orin direct sunlight.

If the stroller chassis parts have been exposed to salt water we recommend that they be rinsed down with soapy water as soon as possible, afterwards clean with a sponge.
Do not fold or store the product while wet and never store a damp environment as this can cause mildew to form.

If you need help or have damaged or missing parts, call the **Customer Helpline:03456 400 800**
This pushchair has been designed to comply with the EN1888:2012.
Country of origin: China
Argos LTD, 489-499 Avebury Boulevard, Central Milton Keynes, MK9 2NW